

Operating Instructions

WARNING

**DO NOT ATTEMPT
TO ALTER OR
REMOVE
COMPONENTS OF
THE SAFE. CONTACT
THE FACTORY AT
817-561-9095 BEFORE
REMOVING**

Thank you for purchasing a new safe. You have selected the finest protection available for your guns, cash, jewelry, camera equipment, and other valuables. Your new safe is designed and built to provide you with a lifetime of trouble free security for your valuables. The following information is your guide to the correct operation and care of your new safe.

LOCK OPERATING INSTRUCTIONS: Please refer to lock instruction sheet in packet.

CLOSING THE SAFE DOOR WARNING: Make sure the door is clear of your hands and fingers before shutting the door. An injury could occur. Grasp the safe handle and make sure the locking bolts

are retracted. Hold slight right (clockwise) pressure on the handle and gently close door. If locking bolts are not fully retracted when you are closing the door, the locking bolts may contact and damage the paint finish. Rotate handle to the left (counter-clockwise) and locking bolts will engage.

ABOUT THE PAINT FINISH- The paint finish on your safe has been custom formulated specifically for this product. It is a powder coat process that is very tough, durable and attractive. To clean the safe, simply spray the surface with a good glass cleaner, such as Windex and wipe with a clean cloth.

INSTALLING THE SAFE- Select where you want your safe positioned and set it in place. Once positioned, we recommend it be anchored to the floor for additional safety and security. Locate the 7/16 inch anchoring holes in the bottom plate of the safe. Lift up interior floor pieces to access the pre-drilled anchoring holes. Determine if you will be anchoring into a wood or concrete floor. Use 3/8 inch diameter lag bolts if you are anchoring into a wood floor. The length of the lag bolts will be determined by the thickness of the floor but try to use at least 2 inches long.

If you are anchoring into a concrete floor, use 3/8 expanding head anchoring bolts, which are at least 2 inches long. The holes for the anchors can be drilled through the 7/16 inch holes that are in the bottom plate of the safe. You do not need to move the safe to install the anchoring bolts.

Note: After the anchor bolts are installed, carefully open and close the safe door and check for smooth operation of the locking mechanism. If any resistance is encountered, check the safe for being level.

WARNING: The safe must be bolted to the floor before use. Serious injury could occur if the safe is not bolted down. If the safe is sitting on carpet or an uneven surface, it could topple over when the door is opened.

WARNING: Do not remove the door under any circumstances. The door is extremely heavy and cumbersome. It is virtually impossible to reinstall without damaging the paint surface.

Where is the safe serial number located? The serial number to your safe is located on the right, bottom front of or your, the back of the safe and inside door frame.

Who do I contact if I lose my combination? Fax a notarized letter which states that you are the owner of the safe along with a serial number to 817-478-3056. We will take a \$25 payment over the phone by credit/debit card and release the code to you.